
# **Split System Heat Pump Water Heater**

HP300S2-F7 (This kit contains the models: THP300S2 & EHP50 S2-F7)



90003373B- The models shown in this Specification Guide (SG) may not be available in all markets and are subject to change at any time. Product specifications may vary from those shown. This SG should not be used as installation guidance for any product. Further information is required to safely and correctly install the products featured here. Specific installation guidance will be available with the product on delivery and on our website haierhome.com

Haier

**Features** 

## Haier


# Split System Heat Pump Water Heater

## THP300S2-F7

Model	THP300S2-F7
Total water capacity	276L
PTR valve setting	700kPa
Hot & cold inlet connections	RP 3⁄4"
PTR connection	RP 3⁄4"
Power input of electric element	2.6kW
Inlet water pressure	100-500kPa
Ambient temperature range	-15~45°C
Dimensions and connections	
Product dimensions	W580xD622xH1694mm

### Note

The power supply for the appliance, and the communication cable are connected via the outdoor heat pump unit.




1694 mm

1410 mm

TOP VIEW

90003373B - The models shown in this Specification Guide (SG) may not be available in all markets and are subject to change at any time. Product specifications may vary from those shown. This SG should not be used as installation guidance for any product. Further information is required to safely and correctly install the products featured here. Specific installation guidance will be available with the product on delivery and on our website haierhome.com



#### SIDE VIEW

# **Split System Heat Pump Water Heater**

## EHP50S2-F7

Haier

Model	EHP50S2-F7									
Rated power input of the heat pump	1.19kW	<u>A</u>	A	λ			A 6	A 6		
Maximum power input of the heat pump	1.7kW	Ę	Ę		E	Ę	<u>ε</u>	<u>ε</u>	<u>الم</u>	Ę
Rated voltage/frequency	220 - 240 V, 50 Hz	123 mm	123 r	123 1						
Max./Rated power input of the appliance	4.3kW	↓	V		V L					√ [
Max./Rated operation current	20A									
COP*@ 20°C/15°C	4.48									
Pair coil tube and connection size - Liquid line	1/4" (6.35mm) / (7/16 - 20UNF)									
Pair coil tube and connection size - Suction line	3/8" (9.52mm) / (5/8 - 18UNF)									
Default temperature setting	55°C					TC	TOP VIEW	TOP VIEW	TOP VIEW	TOP VIEW
Heating range (with element)	35°C – 75°C									
Heating range (heat pump only)	35°C – 55°C									
Refrigerant type / weight	R32/0.93kg	WALL	WALL	WALL	WALL	WALL	WALL	WALL	WALL	WALL
Refrigerant pipe length	min. 1 m - max. 8 m	>200 mm <	>200 mm	>200 mm	>200 mm	>200 mm				
Pre-charged pipe length	5 m									
Sound power level	52dB									
Operation temperature range	-15~45°C									
Recovery time (@ 19°C air temp, 15°C water temp)	2.5 hours									
Recovery time (@ 2°C air temp, 8°C water temp)	4.4 hours									
Dimensions and connections										
Product dimensions	W780xD286xH545mm									
Product weight	30kg						780 mm	780 mm	780 mm	780 mm
Packaged weight	33kg					FRO	FRONT VIE	FRONT VIEW	FRONT VIEW	FRONT VIEW

90003373B - The models shown in this Specification Guide (SG) may not be available in all markets and are subject to change at any time. Product specifications may vary from those shown. This SG should not be used as installation guidance for any product. Further information is required to safely and correctly install the products featured here. Specific installation guidance will be available with the product on delivery and on our website haierhome.com

